

TRACTOPRESS

Cutting ring assembly device with automatic pressure adjustment



Features / Equipment

- Compact and rugged table-top unit for mobile and flexible use
- Assembly of most customary single-bite and double-bite cutting rings
- Proof and leakage-free assembling due to automatic pressure adjustment
- Integrated cooling for hydraulic oil
- Short assembling times of only few seconds
- Short set-up times when changing the tube diameter



Options

- Storage box for clear depositing of the tools (assembling connections and counter-support plates)

Useful accessory:
Storage box for the tooling.

Technical Data

Tube diameter range (OD)	6 - 42 mm
Hydraulics	3,7 l/min
Capacity of the hydraulic tank	3 l
Maximum hydraulic pressure	205 bar
Feed rate of the piston	9,3 mm/s
Dimensions (WxHxD)	450 x 300 x 500 mm
Weight, approx.	55 kg
Power requirement	1,2 kW

Subject to technical alteration • 2009-08



THE ONLY CHOICE
FOR PERFECT
PIPE FABRICATION

TRACTO-TECHNIK GmbH & Co. KG Spezialmaschinen
Hunold-Rump-Str. 76-80 · D-57368 Lennestadt
Tel: +49 (0) 27 25 / 95 40 - 0 · Fax: +49 (0) 27 25 / 95 40 - 39
www.tracto-technik.de · E-Mail: tubomat@tracto-technik.de