

VARIOMAT

Combined tube working device for cutting ring assembly and flaring




VARIOMAT
with cutting ring assembly unit



VARIOMAT
with flaring unit

Features / Equipment

- Compact and rugged table-top unit for mobile and flexible use
- Very well suited for both, assembly of most cutting rings and flaring (37° SAE, 10°) of tubes with \varnothing 6 - 42 mm
- Clearly arranged schedule allows for selecting the specific hydraulic pressure (according to the tube diameter and the working method)
- Manual pressure adjustment with digital display
- Short assembling times of only few seconds
- Short set-up times when changing the tube diameter or the working method



Regardless which connection method is favourite to you:

The VARIOMAT is the professional solution for both connections.

Options

- Storage box for cutting ring assembly tooling (assembling connections and counter-support plates)

Technical Data

Tube diameter range (OD)	6 - 42 mm
Hydraulics	3,7 l/min
Capacity of the hydraulic tank	3 l
Maximum hydraulic pressure	200 bar
Feed rate of the piston	7,5 mm/s
Dimensions (WxHxD)	535 x 285 x 500 mm
Weight, approx.	65 kg
Power requirement	1,2 kW

Subject to technical alteration • 2009-08



THE ONLY CHOICE
FOR PERFECT
PIPE FABRICATION

TRACTO-TECHNIK GmbH & Co. KG Spezialmaschinen
Hunold-Rump-Str. 76-80 · D-57368 Lennestadt
Tel: +49 (0) 27 25 / 95 40 - 0 · Fax: +49 (0) 27 25 / 95 40 - 39
www.tracto-technik.de · E-Mail: tubomat@tracto-technik.de